



RAFFA'S

UNDERBAR FRIDGES

RAFFAS.CO.ZA



EQUIPMENT

UNDERBAR FRIDGE



STAYCOLD

SDU2000

SLIDING GLASS DOOR UNDERBAR

SPECIFICATIONS

CAPACITY:	659 LT
SHELVES:	4 (2 PER DOOR)
COOLING TYPE:	FORCED AIR
VOLTAGE / HZ:	220/50
SET -POINT TEMP:	2°C
EXTERNAL DIMENSIONS:	900 X 2000 X 645MM
INTERNAL DIMENSIONS:	900 X 2000 X 645MM



STAYCOLD

HDU1800-HC

GLASS DOOR UNDERBAR

SPECIFICATIONS

CAPACITY:	612 LT
SHELVES:	6 (2 PER DOOR)
COOLING TYPE:	FORCED AIR
VOLTAGE / HZ:	220/50
EXTERNAL DIMENSIONS:	900 X 1800 X 750MM
INTERNAL DIMENSIONS:	690 X 1400 X 655MM



STAYCOLD

HDU1800-PHC

GLASS DOOR UNDERBAR WITH PIZZA TOP

SPECIFICATIONS

CAPACITY:	612 LT
SHELVES:	6 (2 PER DOOR)
COOLING TYPE:	FORCED AIR
VOLTAGE / HZ:	220/50
SET -POINT TEMP:	2°C
EXTERNAL DIMENSIONS:	915 X 1800 X 750MM
INTERNAL DIMENSIONS:	690 X 1400 X 655MM

EQUIPMENT

UNDERBAR FRIDGE



STAYCOLD

SHDU1800-HC
SOLID DOOR UNDERBAR
SPECIFICATIONS

CAPACITY:	612 LT
SHELVES:	6 (2 PER DOOR)
COOLING TYPE:	FORCED AIR
VOLTAGE / HZ:	220/50
SET -POINT TEMP:	2°C
EXTERNAL DIMENSIONS:	900 X 1800 X 750MM
INTERNAL DIMENSIONS:	690 X 1400 X 655MM



STAYCOLD

SHDU1800-PHC
SOLID DOOR UNDERBAR WITH PIZZA TOP
SPECIFICATIONS

CAPACITY:	612 LT
SHELVES:	6 (2 PER DOOR)
COOLING TYPE:	FORCED AIR
VOLTAGE / HZ:	220/50
SET -POINT TEMP:	2°C
EXTERNAL DIMENSIONS:	915 X 1800 X 750MM
INTERNAL DIMENSIONS:	690 X 1400 X 655MM



FRIDGE STAR

EB1850SG/SS (OPTION WITH PIZZA TOP)
2.5 SWING GLASS/SOLID DOOR UNDERBAR FRIDGE R290
S/S EXTERIOR CASTOR WHEELS ELECTRONIC
SPECIFICATIONS

CAPACITY:	610 LT
SHELVES:	2
ENERGY CONSUMPTION KWH/24HR:	3.59
TEMPERATURE RANGE:	2 - 7°C
DIMENSIONS:	915 X 1830 X 785MM



FRIDGE STAR

EB2550SG/SS (option with pizza top)
3.5 SWING GLASS/SOLID DOOR UNDERBAR FRIDGE R290
S/S EXTERIOR CASTOR WHEELS ELECTRONIC
SPECIFICATIONS

CAPACITY:	853 LT
SHELVES:	3
ENERGY CONSUMPTION KWH/24HR:	3.84
TEMPERATURE RANGE:	2 - 7°C
DIMENSIONS:	915 X 2415 X 785MM

UNDERBAR FRIDGES - SOLID DOOR

FEATURES

- Temperature range 2°C - 6°C
- 4 Swivel castors, 2 with brake
- Digital temperature controller
- Spring loaded door mechanism
- Automatic defrosting
- 1 Shelf per full door
- Fitted with Embraco compressor
- Full S/Steel interior



1 AND HALF DOOR UFS7012-R02

SPECIFICATIONS	
POWER	: 2.5 kW
VOLTAGE	: 230V~/50Hz
UNIT	: 1180 X 750 X 900MM
WEIGHT	: 86KG
TEMPERATURE	: 2°C - 6°C
CAPACITY	: 320LT
SHELVES	: 1 per full door



2 AND HALF DOOR UFS7018-R02

SPECIFICATIONS	
POWER	: 2.5 kW
VOLTAGE	: 230V~/50Hz
UNIT	: 1780 X 750 X 900MM
WEIGHT	: 110KG
TEMPERATURE	: 2°C - 6°C
CAPACITY	: 550LT
SHELVES	: 1 per full door



3 AND HALF DOOR UFS7024-R02

SPECIFICATIONS	
POWER	: 3 kW
VOLTAGE	: 223V~/50Hz
UNIT	: 2380 X 750 X 900MM
WEIGHT	: 139KG
TEMPERATURE	: 2°C - 6°C
CAPACITY	: 780LT
SHELVES	: 1 per full door

UNDERBAR FRIDGES - PIZZA TOP - SOLID DOOR

FEATURES

- Temperature range 2°C - 6°C
- 4 Swivel castors, 2 with brake
- Digital temperature controller
- Spring loaded door mechanism
- Automatic defrosting
- 1 Shelf per full door
- Fitted with Embraco compressor
- Full S/Steel interior



2 AND HALF DOOR UPS7018-R02

SPECIFICATIONS	
POWER	: 2.5 kW
VOLTAGE	: 230V~/50Hz
UNIT	: 1780 X 750 X 900MM
WEIGHT	: 110KG
TEMPERATURE	: 2°C - 6°C
CAPACITY	: 550LT
SHELVES	: 1 per full door



3 AND HALF DOOR UPS7024-R02

SPECIFICATIONS	
POWER	: 3 kW
VOLTAGE	: 230V~/50Hz
UNIT	: 2380 X 750 X 900MM
WEIGHT	: 139KG
TEMPERATURE	: 2°C - 6°C
CAPACITY	: 780LT
SHELVES	: 1 per full door

OTHER ORDER CODES

INSERTS

INT2065 - 1/3
INS9150, INS2100, INS2065 - 1/6
INN9100 - 1/9

NOTE

Inserts not included



FEATURES

- Black units - Outer cabinet manufactured from coated mild steel
- Stainless steel units - Outer cabinet manufactured stainless steel
- High pressure injected 40mm cyclopentane insulation
- Cabinet interior manufactured from compressed aluminium
- 14W square fan assisted condenser
- Automatic defrost function
- Doors are fitted with tempered glass
- Fitted with adjustable feet for easy leveling
- Fitted with a digital temperature control and display
- Smooth action sliding doors / hinged doors
- Standard with internal LED lights and locks



3 DOOR

SPECIFICATIONS

MODEL PolarCab LG320
ELECTRICITY 0.67kW, 220V, Single Phase
EXTERNAL DIMENSIONS 1350 x 520 x 850mm high
WEIGHT 80kg
INTERNAL DIMENSIONS 1260 x 385 x 700mm high
GROSS VOLUME 320Lt
TEMP RANGE 2 to 10°C
REFRIGERANT GAS R600a
SHELVES SUPPLIED (6x) 400 x 345mm

SLIDING DOORS - BLACK BBP2003
HINGED DOORS - BLACK BBP1003
HINGED DOORS - S/STEEL BBP3003



2 DOOR

SPECIFICATIONS

MODEL PolarCab LG198
ELECTRICITY 0.23kW, 220V, Single Phase
EXTERNAL DIMENSIONS 900 x 520 x 850mm high
WEIGHT 62kg
INTERNAL DIMENSIONS 820 x 385 x 700mm high
GROSS VOLUME 198Lt
TEMP RANGE 2 to 10°C
REFRIGERANT GAS R600a
SHELVES SUPPLIED (4x) 400 x 345mm

SLIDING DOORS - BLACK BBP2002
HINGED DOORS - BLACK BBP1002
HINGED DOORS - S/STEEL BBP3002



SINGLE DOOR

SPECIFICATIONS

MODEL PolarCab LG128
ELECTRICITY 0.18kW, 220V, Single Phase
EXTERNAL DIMENSIONS 600 x 520 x 850mm high
WEIGHT 46kg
INTERNAL DIMENSIONS 520 x 385 x 700mm high
GROSS VOLUME 128Lt
TEMP RANGE 2 to 10°C
REFRIGERANT GAS R600a
SHELVES SUPPLIED (2x) 500 x 345mm

HINGED DOOR - BLACK BBP1001
HINGED DOOR - S/STEEL BBP3001



DIGITAL TEMPERATURE CONTROL AND DISPLAY