



RAFFA'S

DOUGH PROOFERS

RAFFAS.CO.ZA





FEATURES

- Manufactured from 201 stainless steel
- Polyurethane foam insulation
- Fitted with a fan circulation system, more uniform proofing effect
- Automatic hydration system - inlet and outlet
- Micro-computer /digital display control panel with timing function
- Big tempered glass windows for improved viewing of the proofing process
- Fitted with (4x) castors

32 TRAY

SPECIFICATIONS

| | |
|-------------|---------------------------|
| MODEL | BakeMark XF32B |
| ELECTRICITY | 3.2kW, 230V, Single Phase |
| DIMENSIONS | 1020 x 820 x 1980mm high |
| WEIGHT | 110kg |
| CAPACITY | (32x) 600 x 400mm trays |
| TEMP RANGE | 20 to 60°C |
| HUMIDITY | 80 to 90% |



ORDER CODE

PCB-XF32B

16 TRAY

SPECIFICATIONS

| | |
|-------------|---------------------------|
| MODEL | BakeMark XF16B |
| ELECTRICITY | 2.4kW, 230V, Single Phase |
| DIMENSIONS | 500 x 770 x 1980mm high |
| WEIGHT | 55kg |
| CAPACITY | (16x) 600 x 400mm trays |
| TEMP RANGE | 20 to 60°C |
| HUMIDITY | 80 to 90% |



ORDER CODE

PCB-XF16B



FEATURES

- Manufactured from 201 stainless steel
- Polyurethane foam insulation
- Fitted with a fan circulation system, more uniform proofing effect
- Automatic hydration system - inlet and outlet
- Manual control panel with timing function
- Tempered glass window for improved viewing of the proofing process
- Fitted with (4x) castors
- Stackable with the BakeMark RX6D convection oven

10 TRAY

SPECIFICATIONS

| | |
|----------------|-------------------------|
| MODEL | BakeMark XF10 |
| ELECTRICITY | 3kW, 230V, Single Phase |
| DIMENSIONS | 930 x 1200 x 750mm high |
| WEIGHT | 80kg |
| CAPACITY | (10x) 600 x 400mm trays |
| RUNNER SPACING | 80mm |
| TEMP RANGE | 20 to 60°C |
| HUMIDITY | 80 to 90% |



ORDER CODE

PCB-XF10



STACKABLE

OPTIONAL EXTRAS

BAKING TRAY
600 x 400 x 30mm

BTA0064

OVEN GRIDS
600 x 400mm

OGS0064

COOLING RACK
600 x 400mm

CTS0064